

NOTES:

- 1. HYDRANT TO BE KENNEDY TYPE K-81 (NO EQUAL). COORDINATE WITH CITY OF PORTSMOUTH WATER AND FIRE DEPARTMENT.
- 2. HYDRANT SHALL OPEN RIGHT (CITY OF PORTSMOUTH) AND OPEN LEFT (PEASE TRADEPORT).
- 3. HYDRANT SHALL BE PAINTED IN ACCORDANCE WITH CITY OF PORTSMOUTH STANDARDS.
- 4. AREA AROUND HYDRANT SHALL BE GRADED TO ALLOW SURFACE WATER TO DRAIN AWAY.

- CONTRACTOR SHALL INSTALL AN INDICATOR ATTACHED TO THE HYDRANT IN ACCORDANCE TO CITY OF PORTSMOUTH STANDARDS.
- 6. HYDRANT ASSEMBLY SHALL BE POLY WRAPPED FROM MAIN TO HYDRANT AT GROUND LEVEL, 6" (MIN.) OF SAND FOR BEDDING AND COVER, WARNING TAPE 18" ABOVE PIPE.
- 7. DRAIN HOLES ARE NOT PERMITTED.

FIRE HYDRANT SCALE: N.T.S

CITY OF
PORTSMOUTH
STANDARD
TECHNICAL
SPECIFICATIONS NH

DEPARTMENT OF PUBLIC WORKS OF PORTSMOUTH, 680 PEVERLY HILL ROAD 603-427-1530 CITY



05/09/2025 N/A PHR ΒΥ: APVD

DATE: OB SCALE: NG PROJ. NO.:

CITY OF PORTSMOUTH STANDARD DETAILS HYDRANT FIRE

SHEET: W - 004